

WXD2010



Item No: WXD2010N

2-Channel Solder- and Desoldering
Station, 200 W (255 W)

KEY FEATURES

- + Desoldering station WXD 2, 2 channels with desoldering iron WXDP 120
- + Connection to external compressed air supply required
- + Energy effective: automatic stand-by mode for tools
- + Patented, ESD safe glass display. Simple and fast setting of soldering parameter

TECHNICAL DATA

Length	6.6 in
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	35 l/min
Air Pressure	58 - 87 psi
Compressed Air Connection (Outer Diameter)	6.0mm
Compressed Air Connection Accessory	Oil free, dry compressed air
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°C) Adjustable temperature range varies among tools
Temperature Range °C	50 - 550 °C
Temperature Range °F	200 - 850 °F
Tip Type	WX
UPC	037103305268
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Vacuum	0.5 bar (55 kPA) (8 psi)
Voltage	120 V
Weight (Catalog)	3.20 kg
Product Family	Rework, Hot Air, Desoldering Stations