

1089515

https://www.phoenixcontact.com/us/products/1089515

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Tool set for GOF assembly

Product description

Tool set for GOF assembly, for field installation of LC and SC connectors. Thanks to cleave technology, it is no longer necessary to bond and polish the connectors.

Your advantages

- · Suitable for quick and easy field assembly or repair
- · Cleave technology
- · No bonding or polishing
- · Optimum attenuation values with easy assembly
- · A real alternative to splicing
- · Reusable connectors

Commercial data

Item number	1089515
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB15
Product key	ABNIEY
GTIN	4055626894041
Weight per piece (including packing)	1,700 g
Weight per piece (excluding packing)	1,700 g
Customs tariff number	82060000
Country of origin	BG



1089515

https://www.phoenixcontact.com/us/products/1089515

Set consists of

FOC-TOOL-CASE-EMPTY - FO accessories

1414095

https://www.phoenixcontact.com/us/products/1414095



Replacement case, empty

FOC-TOOL-FIBERCLAMP - FO accessories

1414096

https://www.phoenixcontact.com/us/products/1414096

Wire holder





1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-TOOL-LIGHTSOURCE-ADAPTER - FO accessories

1414097

https://www.phoenixcontact.com/us/products/1414097



Red light source adapter

FOC-TOOL-LIGHTSOURCE-650 - FO accessories

1414098

https://www.phoenixcontact.com/us/products/1414098



Red light source (650 nm)



1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-TOOL-STRIPPING-FA-1 - FO accessories

1414099

https://www.phoenixcontact.com/us/products/1414099

2-hole fiber stripper



FOC-TOOL-STRIPPING-FA-2 - FO accessories

1414100

https://www.phoenixcontact.com/us/products/1414100

Fiber stripper for AWG 22 - 10 / (0.6 ... 2.6 mm)





1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-TOOL-FIBERCONTAINER - FO accessories

1414102

https://www.phoenixcontact.com/us/products/1414102





FOC-TOOL-CLEANINGWIPE - FO accessories

1414104

https://www.phoenixcontact.com/us/products/1414104

Fiber cleaning cloth





1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-TOOL-MARKER BK - FO accessories

1414105

https://www.phoenixcontact.com/us/products/1414105



Marker pen

FOC-SC-LC-OM4-LS-CABLE/3 - FO accessories

1414106

https://www.phoenixcontact.com/us/products/1414106

Launch fiber multimode





1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-SC-LC-OS2-LS-CABLE/3 - FO accessories

1414107

https://www.phoenixcontact.com/us/products/1414107

Launch fiber single mode (OS2)



FOC-TOOL-STRIPPING-MARKER - Distribution block

1218483

https://www.phoenixcontact.com/us/products/1218483

Marker for stripping FO cables





1089515

https://www.phoenixcontact.com/us/products/1089515

CUTFOX-ES - Cutting tool

1212621

https://www.phoenixcontact.com/us/products/1212621



Electrician's scissors, high cutting performance thanks to micro-serrated cutting area, suitable for copper, aluminum, Kevlar fibers, and plastic, two-component non-slip soft-grip handles, ergonomic design, adjustable screw joint

FOC-TOOL-CLEAVER-HOLDER-UNIVERSAL - Accessories for tools

1218486

https://www.phoenixcontact.com/us/products/1218486

Holder for cleaving tool for multimode and singlemode connectors





1089515

https://www.phoenixcontact.com/us/products/1089515

FOC-TOOL-CLEAVER-UNIVERSAL - Distribution block

1218485

https://www.phoenixcontact.com/us/products/1218485

Cleaver for assembly of FO connectors





1089515

https://www.phoenixcontact.com/us/products/1089515

Technical data

Product properties

Product type	Assembly tool	
Dimensions		
Width	34.5 cm	
Height	6.5 cm	
Length	28 cm	
Material specifications		

N

riodollig material	Housing material	Plastic
--------------------	------------------	---------

Cable/line

Cable type	for all common STB cable types, TB limited
FO cable	
Transmission medium	FO

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C 70 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Ambient temperature (assembly)	0 °C 50 °C

Mounting

Moun	ting type	mechanical splice



1089515

https://www.phoenixcontact.com/us/products/1089515

Classifications

ECLASS

	ECLASS-13.0	21049090
Εī	ГІМ	
	ETIM 9.0	EC011823
UNSPSC		
	UNSPSC 21.0	39121400



1089515

https://www.phoenixcontact.com/us/products/1089515

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com