

SIMATIC IPC277E (Nanopanel PC); 15" Multitouch (1366 x 768); 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 3x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply; Celeron N2807 (2C/2T) 4 GB RAM; Windows 10 IoT Enterprise LTSB 2016, 64 bit, MUI (en,de,fr,it,es) 256 GB Eco SSD; without SIMATIC software

General information	
Product type designation	IPC277E
Display	
Design of display	15" TFT multi-touch
Screen diagonal	15 in
Resolution (pixels)	
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	70 000 h
Control elements	
Touch operation	
• Design as multi-touch screen	Yes; Projective-capacitive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	46 W
Dimensions	
Width of the housing front	398 mm
Height of housing front	257 mm
Mounting cutout, width	382 mm
Mounting cutout, height	241 mm
Overall depth	76 mm
Weights	
Weight, approx.	5.5 kg
Classifications	

	Version	Classification
eClass	14	19-20-01-03
eClass	12	19-20-01-03
eClass	9.1	19-20-01-03
eClass	9	19-20-01-03
eClass	8	27-24-23-01
eClass	7.1	27-24-23-01
eClass	6	27-24-23-01
ETIM	9	EC001414
ETIM	8	EC001414
ETIM	7	EC001414

Approvals / Certificates	
General Product Approval	Marine / Shipping



[Manufacturer Declaration](#)

[KC](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)



Dangerous goods

Environment

[Dangerous goods information](#)

[Environmental Confirmations](#)

last modified:

6/25/2021 