SIEMENS

Data sheet

US2:52BP3CT



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 12V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
color of the actuating element	amber
material of the actuating element	plastic
type of unlocking device	without
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
Contact block/ lampholder	
socket design	BA 9s with lamp
number of lampholders	1
Display	
number of LED modules	0
General technical data	
product component	
lamp transformer	No
light source	Yes
degree of pollution	1
type of voltage	
 of the operating voltage 	AC/DC
 of the input voltage 	AC/DC
surge voltage resistance rated value	4 kV
protection class IP	IP66
protection class IP of the terminal	IP20
Weight	0.23 kg
operating voltage	
• at AC at 60 Hz rated value	12 13 V
• at DC rated value	12 13 V
Supply voltage	
type of voltage of the supply voltage of the light source	AC/DC
supply voltage of the light source at AC at 60 Hz rated value	

•	12 V	
supply voltage of the light source at DC rated value		
•	12 V	
Connections/ Terminals		
type of electrical connection	screw terminal	
 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket maximum	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
type of light source	filament lamp	
color of the light source	clear	
Electrical Safety		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Further information		
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875		
Information- and Downloadcenter (Catalogs, Brochures,)		
https://www.siemens.com/ic10		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3CT		
Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3CT		
Service&Support (Manuals, Certificates, Characteristics, FAQs,)		
https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3CT		
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3CT⟨=en		

last modified:

4/8/2024 🖸