1202580

https://www.phoenixcontact.com/us/products/1202580



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assortment box, metal, supplied with ferrules acc. to DIN 46228-4, 300 pcs. AI 10-12 RD, 200 pcs. AI 16-12 BU, 100 pcs. AI 25-16 YE, as well as WIREFOX-D 40 stripping blade, CRIMPFOX 25R crimping pliers

Product description


Tool set, equipped

Your advantages

· We have put together a number of attractive tool sets for you by selecting products from our comprehensive range of professional tools

Commercial data

Item number	1202580
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH3511
Catalog page	Page 471 (C-3-2019)
GTIN	4017918017934
Weight per piece (including packing)	3,075 g
Weight per piece (excluding packing)	2,948 g
Customs tariff number	82060000
Country of origin	SE



1202580 https://www.phoenixcontact.com/us/products/1202580



Set consists of

AI 10 -12 RD - Ferrule

3200551 https://www.phoenixcontact.com/us/products/3200551

Ferrule, Length contact range: 12 mm, sleeve length: 22 mm, color: red



AI 16 -12 BU - Ferrule

3200564 https://www.phoenixcontact.com/us/products/3200564



Ferrule, Length contact range: 12 mm, sleeve length: 24 mm, color: blue

1202580

https://www.phoenixcontact.com/us/products/1202580



AI 25 -16 YE - Ferrule

3200577

https://www.phoenixcontact.com/us/products/3200577



Ferrule, Length contact range: 16 mm, sleeve length: 30 mm, color: yellow

WIREFOX-D 40 - Stripping tool

1212161 https://www.phoenixcontact.com/us/products/1212161



Stripping tool, for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

1202580 https://www.phoenixcontact.com/us/products/1202580



CRIMPFOX 25R - Crimping pliers

1212039

https://www.phoenixcontact.com/us/products/1212039



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 10 mm² ... 25 mm², lateral entry, WM crimp

1202580

https://www.phoenixcontact.com/us/products/1202580



May 22, 2025, 3:22 PM Page 5 (7)

Technical data

Base element material

Notes

Environmental Product Compliance				
California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration			
Product properties				
Product type	Tool set			
Compression	WM crimp			
Dimensions				
Width	357 mm			
Height	48 mm			
Length	206 mm			
Material specifications				
Color	silver/matt			

Metal

1202580

https://www.phoenixcontact.com/us/products/1202580



Classifications

ECLASS

	ECLASS-13.0	27400218		
ETIM				
	ETIM 9.0	EC000524		
UNSPSC				
	UNSPSC 21.0	39121400		

1202580

https://www.phoenixcontact.com/us/products/1202580



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com