

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2x), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

## Commercial data

Item number	1139022
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBBFC
GTIN	4063151086510
Weight per piece (including packing)	244 g
Weight per piece (excluding packing)	182 g
Customs tariff number	85371091
Country of origin	DE

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

## Technical data

### Product properties

Product type	AC charging controller
Product family	CHARX control modular
Design	with Embedded Linux system
Operating mode	Stand-Alone
	Client
	Server
Charging standard	IEC 61851-1
Charging mode	Mode 3, Case B + C

### Insulation characteristics

Overvoltage category	III
----------------------	-----

### System properties

#### IEC 61131 runtime system

Data storage system	8 GByte (eMMC)
---------------------	----------------

### Electrical properties

#### Supply

Supply voltage	12 V DC $\pm 5\%$
Supply voltage range	11.4 V DC ... 12.6 V DC
Max. current consumption	2 A (Stand-alone operation)

### Input data

#### Digital

Number of digital inputs	4
Description of the input	Digital input
Nominal input voltage $U_N$	12 V
Input voltage range $U_1$	0 V ... 3 V (Off)
Input voltage range $U_2$	9 V ... 15 V (On)

### Output data

#### Digital

Output name	Digital output
Number outputs	4
Maximum output voltage	$\leq 12$ V (Low-side operation)
Maximum output current	max. 600 mA

### Connection data

#### Conductor connection

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

Connection method	pluggable
	Push-in technology
Conductor cross section rigid	0.14 mm² ... 1.5 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 16

## Interfaces

Interface	Ethernet (2x)
	CHARX control modular system bus
	USB-C

### Ethernet

Interface	Ethernet
Connection method	RJ45 jack
Number of interfaces	2
Number of supported devices	2
Serial transmission speed	10/100 Mbps
Transmission length	100 m
Protocols supported	OCPP 1.6J
	Modbus/TCP
	MQTT
	HTTP
	HTTPS

### Others

Interface	Configuration and diagnostics
Connection method	USB type C
Number of interfaces	1
Protocols supported	RNDIS

### Others

Interface	Energy meter
Bus system	RS-485
Transmission speed range	9.6 kbps ... 115.2 kbps (Automatic setting in accordance with the selected energy meter)

### Others

Interface	RFID readers
Bus system	RS-485
Transmission speed range	9.6 kbps ... 115.2 kbps (Automatic setting in accordance with the selected RFID reader)

### Others

Interface	CHARX control modular system bus
Connection method	DIN rail bus connector
Number of interfaces	1

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	58 kPa ... 106 kPa (up to 4500 m above mean sea level)

## Approvals

### Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

## Standards and regulations

### Standards

Standards/regulations	IEC 61851-1
-----------------------	-------------

## Mounting

Mounting type	DIN rail mounting
Assembly note	DIN rail mounting
Mounting position	any

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

## Classifications

### ECLASS

ECLASS-13.0	27144703
-------------	----------

### ETIM

ETIM 9.0	EC002889
----------	----------

### UNSPSC

UNSPSC 21.0	39121800
-------------	----------

# CHARX SEC-3000 - AC charging controller



1139022

<https://www.phoenixcontact.com/us/products/1139022>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

### China RoHS

Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2ba36988-27cf-4fff-b7a9-1df9fd9e7f32

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)