

SlimSAS™ Connectors – U10 Series

PROVEN, HIGH SPEED, NEXT-GENERATION SAS-4 INTERFACE

SlimSAS™ connectors address issues in next-generation storage devices such as bulk cable form factor restrictions and the introduction of multi-lane storage devices.

SlimSAS™ connector is a 0.60mm pitch interconnect system which offers superior signal integrity performance over standard Mini-SAS solutions.

- Designed for unshielded, internal or external I/O connectors
- Compliant with T10/Serial Attached SCSI (SAS-4) standard
- Supports many assembly options



FEATURES

- High density connector
- 0.60mm pitch, 4x, 6x, 8x, 12x configurations
- 8x SlimSAS solution consumes the same area as 4x Mini-SAS HD
- Supports internal and external I/O applications
- Small Form Factor
- High data rate
- Low profile packaging
- Meets SAS 4.0, 24Gb/s specification
- Resonance dampening feature
- Supports many assembly options

BENEFITS

- Low profile connector saves space
- Complete interconnect solution for different applications
- Performance targeted for next-gen SAS 4.0 and PCIe Gen 4
- Receptacle mates pluggable modules
- Supports desired high speed design
- Meets next-generation industry standards
- Customized signal integrity specification and support NVLink 25G
- Supports blade and mainstream server designs

TECHNICAL INFORMATION

MATERIAL

- Housing: Black color, LCP, Lead Free Solder Reflow Process Compatible Thermoplastic
- Contact Base Material: Phosphor Bronze
- Contact Normal Force: 50g nominal
- Plating Solder Tails: Matte tin or Gold flash options
- Plating Mating Tails: Gold
- Resonance Dampening Feature: Conductive Polymer

MECHANICAL PERFORMANCE

- Mating Force: 55.5 N max.
- Durability: 250 mating cycles min.
- Latch Retention Force: 50 N min.
- Insertion Force: 55.5 N
- Withdrawal Force: 49 N

APPROVALS AND CERTIFICATIONS

- UL 94V-0
- RoHS
- Halogen-free

PACKAGING

- Tape & Reel

ELECTRICAL PERFORMANCE

- Voltage Rating: 30VDC per contact max.
- Current Rating: 0.5A per contact max.
- Differential Impedance: $85 \Omega \pm 10 \Omega$

ENVIRONMENTAL

- Operating Temperature: -40°C to $+85^{\circ}\text{C}$

SPECIFICATION

- Amphenol Product Specification: SFF-8654

TARGET MARKETS/APPLICATIONS



Data Center
HBA (Host Bus Adapter) Servers
RAIDS (Redundant Array of Individual
Disks)
Routers
Switches
Servers
Storage Racks
Storage Controllers

PART NUMBER SELECTOR

U10		X	X	XX	X	X	X	XX	T																																
SlimSAS Receptacle									Tape & Reel																																
<table border="1"> <thead> <tr> <th colspan="2">Style</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>X8 Right Angle</td> </tr> <tr> <td>B</td> <td>X8 Vertical</td> </tr> <tr> <td>C</td> <td>X4 Right Angle</td> </tr> <tr> <td>D</td> <td>X4 Vertical</td> </tr> <tr> <td>E</td> <td>X4 Vertical Low Profile</td> </tr> <tr> <td>F</td> <td>X8 Vertical Low Profile</td> </tr> <tr> <td>G</td> <td>X12 Vertical Low Profile</td> </tr> <tr> <td>J</td> <td>X12 Right Angle</td> </tr> <tr> <td>K</td> <td>X12 Vertical</td> </tr> </tbody> </table>		Style		A	X8 Right Angle	B	X8 Vertical	C	X4 Right Angle	D	X4 Vertical	E	X4 Vertical Low Profile	F	X8 Vertical Low Profile	G	X12 Vertical Low Profile	J	X12 Right Angle	K	X12 Vertical								<table border="1"> <thead> <tr> <th colspan="2">Sequence Number</th> </tr> </thead> <tbody> <tr> <td>Blank</td> <td>PN assigned</td> </tr> <tr> <td>01</td> <td>74 Pos</td> </tr> <tr> <td>02</td> <td>38 Pos</td> </tr> </tbody> </table>	Sequence Number		Blank	PN assigned	01	74 Pos	02	38 Pos				
Style																																									
A	X8 Right Angle																																								
B	X8 Vertical																																								
C	X4 Right Angle																																								
D	X4 Vertical																																								
E	X4 Vertical Low Profile																																								
F	X8 Vertical Low Profile																																								
G	X12 Vertical Low Profile																																								
J	X12 Right Angle																																								
K	X12 Vertical																																								
Sequence Number																																									
Blank	PN assigned																																								
01	74 Pos																																								
02	38 Pos																																								
									<table border="1"> <thead> <tr> <th colspan="2">Option</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>Standard (except U10BH74*)</td> </tr> <tr> <td>0</td> <td>No Resonance Dampening for U10BH74*</td> </tr> <tr> <td>1</td> <td>No Resonance Dampening (except U10BH74*)</td> </tr> <tr> <td>1</td> <td>Resonance Dampening for U10BH74*</td> </tr> </tbody> </table>	Option		0	Standard (except U10BH74*)	0	No Resonance Dampening for U10BH74*	1	No Resonance Dampening (except U10BH74*)	1	Resonance Dampening for U10BH74*																						
Option																																									
0	Standard (except U10BH74*)																																								
0	No Resonance Dampening for U10BH74*																																								
1	No Resonance Dampening (except U10BH74*)																																								
1	Resonance Dampening for U10BH74*																																								
									<table border="1"> <thead> <tr> <th colspan="2">Latch Anchor Metal Shell Option</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>Pin 1.5mm long, Right Angle</td> </tr> <tr> <td>1</td> <td>SMT</td> </tr> <tr> <td>3</td> <td>No latch metal shell</td> </tr> <tr> <td>4</td> <td>Pin 2.2mm long, Right Angle</td> </tr> <tr> <td>5</td> <td>Pin 3.0mm long, Right Angle</td> </tr> <tr> <td>6</td> <td>Pin 4.2mm long, Right Angle</td> </tr> <tr> <td>0</td> <td>Pin 1.5mm long, Pin inside footprint on Vertical</td> </tr> <tr> <td>2</td> <td>Pin 1.5mm long, Pin outside footprint on Vertical</td> </tr> <tr> <td>3</td> <td>No Latch</td> </tr> <tr> <td>4</td> <td>Pin 2.2mm long, Pin outside footprint on Vertical</td> </tr> <tr> <td>5</td> <td>Pin 3.0mm long, Pin outside footprint on Vertical</td> </tr> <tr> <td>6</td> <td>Pin 4.2mm long, Pin outside footprint on Vertical</td> </tr> <tr> <td>7</td> <td>Pin 2.2mm long, Pin inside footprint on Vertical</td> </tr> <tr> <td>8</td> <td>Pin 3.0mm long, Pin inside footprint on Vertical</td> </tr> <tr> <td>9</td> <td>Pin 4.2mm long, Pin inside footprint on Vertical</td> </tr> </tbody> </table>	Latch Anchor Metal Shell Option		0	Pin 1.5mm long, Right Angle	1	SMT	3	No latch metal shell	4	Pin 2.2mm long, Right Angle	5	Pin 3.0mm long, Right Angle	6	Pin 4.2mm long, Right Angle	0	Pin 1.5mm long, Pin inside footprint on Vertical	2	Pin 1.5mm long, Pin outside footprint on Vertical	3	No Latch	4	Pin 2.2mm long, Pin outside footprint on Vertical	5	Pin 3.0mm long, Pin outside footprint on Vertical	6	Pin 4.2mm long, Pin outside footprint on Vertical	7	Pin 2.2mm long, Pin inside footprint on Vertical	8	Pin 3.0mm long, Pin inside footprint on Vertical	9	Pin 4.2mm long, Pin inside footprint on Vertical
Latch Anchor Metal Shell Option																																									
0	Pin 1.5mm long, Right Angle																																								
1	SMT																																								
3	No latch metal shell																																								
4	Pin 2.2mm long, Right Angle																																								
5	Pin 3.0mm long, Right Angle																																								
6	Pin 4.2mm long, Right Angle																																								
0	Pin 1.5mm long, Pin inside footprint on Vertical																																								
2	Pin 1.5mm long, Pin outside footprint on Vertical																																								
3	No Latch																																								
4	Pin 2.2mm long, Pin outside footprint on Vertical																																								
5	Pin 3.0mm long, Pin outside footprint on Vertical																																								
6	Pin 4.2mm long, Pin outside footprint on Vertical																																								
7	Pin 2.2mm long, Pin inside footprint on Vertical																																								
8	Pin 3.0mm long, Pin inside footprint on Vertical																																								
9	Pin 4.2mm long, Pin inside footprint on Vertical																																								
									<table border="1"> <thead> <tr> <th colspan="2">Impedance</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>85Ω</td> </tr> <tr> <td>4</td> <td>85Ω enhancement (Right Angle)</td> </tr> </tbody> </table>	Impedance		0	85Ω	4	85Ω enhancement (Right Angle)																										
Impedance																																									
0	85Ω																																								
4	85Ω enhancement (Right Angle)																																								
									<table border="1"> <thead> <tr> <th colspan="2">Number of Positions</th> </tr> </thead> <tbody> <tr> <td>38</td> <td>38 Pos</td> </tr> <tr> <td>74</td> <td>74 Pos</td> </tr> </tbody> </table>	Number of Positions		38	38 Pos	74	74 Pos																										
Number of Positions																																									
38	38 Pos																																								
74	74 Pos																																								
									<table border="1"> <thead> <tr> <th colspan="2">Contact Plating</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>30 μ" Gold Plating over Nickel</td> </tr> <tr> <td>3</td> <td>15 μ" Gold Plating over Nickel</td> </tr> </tbody> </table>	Contact Plating		2	30 μ" Gold Plating over Nickel	3	15 μ" Gold Plating over Nickel																										
Contact Plating																																									
2	30 μ" Gold Plating over Nickel																																								
3	15 μ" Gold Plating over Nickel																																								