

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



3-way signal conditioner with plug-in connection technology for the electrical isolation of analog signals. Input signal: 0 V ... 10 V, output signal: 4 mA ... 20 mA, push-in connection technology

## Product description

Standard signal 3-way signal conditioner with plug-in connection technology for the electrical isolation, conversion, amplification, and filtering of standard signals. The measuring transducer supports fault monitoring and NFC communication.

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2902030       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | C404          |
| Product key                          | DK1121        |
| GTIN                                 | 4046356652025 |
| Weight per piece (including packing) | 106.7 g       |
| Weight per piece (excluding packing) | 98 g          |
| Customs tariff number                | 85437090      |
| Country of origin                    | DE            |

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

## Technical data

### Notes

#### Utilization restriction

|          |   |
|----------|---|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |
|----------|---|

### Product properties

|                 |                    |
|-----------------|--------------------|
| Product type    | Signal conditioner |
| Product family  | MINI Analog Pro    |
| No. of channels | 1                  |
| Type            | Signal conditioner |

#### Insulation characteristics: GB Standard

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Pollution degree     | 2  |

### Electrical properties

|   |  |
|---|--|
| Electrical isolation                          | 3-way isolation                            |
| Electrical isolation between input and output | yes  |
| Limit frequency (3 dB)                        | $\approx \text{---} \downarrow \text{ Hz}$ |
| Protective circuit                            | Transient protection                       |
| Step response (10-90%)                        | $\approx \text{---} \downarrow \text{ ms}$ |
| Maximum temperature coefficient               | 0.01 %/K                                   |
| Temperature coefficient, typical              | 0.01 %/K                                   |
| Maximum transmission error                    | 0.05 % (of final value)                    |

#### Electrical isolation Input/output/power supply

|                          |   |
|--------------------------|---|
| Rated insulation voltage | 300 V <sub>rms</sub>                              |
| Test voltage             | 3 kV AC (50 Hz, 60 s)                             |
| Insulation               | Reinforced insulation according to IEC/EN 61010-1 |

#### Supply

|                             |  |
|-----------------------------|--|
| Nominal supply voltage      | 24 V DC  |
| Supply voltage range        | 9.6 V DC ... 30 V DC (The DIN rail connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, item no. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail in accordance with EN 60715) |
| Typical current consumption | 25 mA (24 V DC)<br>54 mA (12 V DC)   |
| Power consumption           | $\leq 800 \text{ mW}$ (9.6 V DC)   |

### Input data

#### Signal: Voltage

|                  |   |
|------------------|---|
| Number of inputs | 1 |
|------------------|---|

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

|                                   |  |
|-----------------------------------|--|
| Configurable/programmable         | no   |
| Voltage input signal              | 0 V ... 10 V                                       |
| Input resistance of voltage input | $\approx \text{ } \sqcup \text{ } \text{ M}\Omega$ |

## Output data

Signal: Current

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Number of outputs               | 1                                     |
| Configurable/programmable       | no                                    |
| Non-load voltage                | < 17 V                                |
| Current output signal           | 4 mA ... 20 mA                        |
| Max. current output signal      | 22 mA                                 |
| Load/output load current output | $\leq 600 \Omega$ (20 mA)             |
| Ripple                          | < 20 mV <sub>PP</sub> (600 $\Omega$ ) |

## Connection data

|                                  |  |
|----------------------------------|--|
| Connection method                | Push-in connection   |
| Stripping length                 | 10 mm  |
| Conductor cross section rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (with ferrule)<br>0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (without ferrule) |
| Conductor cross section flexible | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>   |
| Conductor cross section AWG      | 24 ... 12 (flexible)   |

## Ex data

|                       |        |
|-----------------------|--------|
| Ex installation (EPL) | Gc     |
|                       | Div. 2 |

## Signaling

|                |                            |
|----------------|----------------------------|
| Status display | Green LED (supply voltage) |
|----------------|----------------------------|

## Dimensions

|        |           |
|--------|-----------|
| Width  | 6.2 mm    |
| Height | 109.81 mm |
| Depth  | 119.2 mm  |

## Material specifications

|  |                 |
|--|-----------------|
| Color  | gray (RAL 7042) |
| Housing material                                       | PBT             |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 2     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 2     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 2     |

## Environmental and real-life conditions

Ambient conditions

|                      |                           |
|----------------------|---------------------------|
| Degree of protection | IP20 (not assessed by UL) |
|----------------------|---------------------------|

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

|   |                               |
|---|-------------------------------|
| Ambient temperature (operation)         | -40 °C ... 70 °C              |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C              |
| Permissible humidity (operation)        | 5 % ... 95 % (non-condensing) |

## Approvals

### CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

### ATEX

|                |                          |
|----------------|--------------------------|
| Identification | Ⓔ II 3 G Ex ec IIC T4 Gc |
| Certificate    | BVS 19 ATEX E 047 X      |

### IECEX

|                |                    |
|----------------|--------------------|
| Identification | Ex ec IIC T4 Gc    |
| Certificate    | IECEX BVS 19.0041X |

### CCC / China-Ex

|                |                 |
|----------------|-----------------|
| Identification | Ex ec IIC T4 Gc |
|----------------|-----------------|

### UL, USA/Canada

|                |                                       |
|----------------|---------------------------------------|
| Identification | UL 508 Listed                         |
|                | Class I, Div. 2, Groups A, B, C, D T6 |
|                | Class I, Zone 2, Group IIC T6         |

### Shipbuilding approval

|             |                   |
|-------------|-------------------|
| Certificate | DNV GL TAA00002UA |
|-------------|-------------------|

### EAC Ex

|                |                                 |
|----------------|---------------------------------|
| Identification | Ex ec IIC T4 Gc                 |
| Certificate    | BY/112 02.01 TP012 103.01 00079 |

### Shipbuilding data

|             |   |
|-------------|---|
| Temperature | B   |
| Humidity    | B   |
| Vibration   | A   |
| EMC         | A   |
| Enclosure   | Required protection according to the Rules shall be provided upon installation on board |

## EMC data

|                               |  |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC directive                                       |
| Noise immunity                | EN 61000-6-2   |
| Note                          | When being exposed to interference, there may be minimal deviations. |

### Noise emission

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-6-4 |
|-----------------------|--------------|

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

## Electrostatic discharge

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

## Electrostatic discharge

|          |   |
|----------|---|
| Comments | Safety measures must be taken to prevent electrostatic discharge. |
|----------|---|

## Electromagnetic HF field

|                       |                          |
|-----------------------|--------------------------|
| Designation           | Electromagnetic RF field |
| Standards/regulations | EN 61000-4-3             |

## Fast transients (burst)

|                       |                         |
|-----------------------|-------------------------|
| Designation           | Fast transients (burst) |
| Standards/regulations | EN 61000-4-4            |

## Surge current load (surge)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-5 |
|-----------------------|--------------|

## Conducted interference

|                       |                         |
|-----------------------|-------------------------|
| Designation           | Conducted interferences |
| Standards/regulations | EN 61000-4-6            |

## Standards and regulations

|                      |                 |
|----------------------|-----------------|
| Electrical isolation | 3-way isolation |
|----------------------|-----------------|

## GB Standard

|                       |             |
|-----------------------|-------------|
| Standards/regulations | GB/T 3836.1 |
|                       | GB/T 3836.3 |
|                       | GB/T 3836.4 |

## Mounting

|                   |   |
|-------------------|---|
| Mounting type     | DIN rail mounting   |
| Assembly note     | The DIN rail connector can be used for bridging the supply voltage. It can be snapped onto a 35 mm EN 60715 DIN rail. |
| Mounting position | any   |


# MINI MCR-2-U-I4-PT - Signal conditioner

2902030

<https://www.phoenixcontact.com/us/products/2902030>

## Drawings

Block diagram



# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2902030>



**DNV GL**

Approval ID: TAA00002UA



**UL Listed**

Approval ID: FILE E 238705



**cUL Listed**

Approval ID: FILE E 238705



**IECEx**

Approval ID: IECEx BVS 19.0041X



**cUL Listed**

Approval ID: E196811



**UL Listed**

Approval ID: E196811



**ATEX**

Approval ID: BVS 19 ATEX E 047 X



**EAC Ex**

Approval ID: TP012 103.01 00079



**CCC**

Approval ID: 2022122310115961

# MINI MCR-2-U-I4-PT - Signal conditioner



2902030

<https://www.phoenixcontact.com/us/products/2902030>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27210120 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002653 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|



## Environmental product compliance

### EU RoHS

|   |              |
|---|--------------|
| Fulfills EU RoHS substance requirements | Yes          |
| Exemption                               | 7(a), 7(c)-I |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |  |
|-------------------------------------|--|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)   |
|                                     | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7) |
| SCIP                                | 18aadd57-da25-4024-bb94-4afde979faae                           |