SIEMENS

Data sheet

6GK5992-2GA00-8AA0

product type designation product description

MM992-2CUC

XR-300 media module

SCALANCE X accessory; Media module MM992-2CUC; 2x 10/100/1000 Mbit/s RJ45 ports, electrical; with securing collar



interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections	
 for network components or terminal equipment / maximum 	2
number of 10/100/1000 Mbit/s RJ45 ports	2
type of electrical connection	
 for network components or terminal equipment 	RJ45
ambient conditions	
ambient temperature	
 during operation 	-40 +70 °C
 during storage 	-40 +85 °C
 during transport 	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Media module with retaining collar
width	60 mm
height	22 mm
depth	100 mm
net weight	0.08 kg
fastening method	latched
 installation in media module slot 	Yes
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
 for hazardous zone 	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213- M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
 for emitted interference 	EN 61000-6-4:2007 (Class A)
 for interference immunity 	EN 61000-6-2:2005

EN 61000-6-2:2005, EN 61000-6-4:2007
Yes
Yes
Yes
Yes
250 у
http://www.siemens.com/simatic-net
https://mall.industry.siemens.com
http://www.siemens.com/industry/infocenter
http://automation.siemens.com/bilddb
http://www.siemens.com/cax
https://support.industry.siemens.com
12/15/2020 🖸