


SPL TR85

Metal Can® TO56

Infrared Laser Diode in TO56 Package



Applications

- Gesture Recognition

Features:

- Laser wavelength 850 nm
- Efficient radiation source for cw and pulsed operation
- Single tranverse mode semiconductor laser
- High modulation bandwidth
- TO56 package with photo diode

Ordering Information

Type	Peak output power typ. $T_{\text{case}} = 25\text{ °C}$ P_{opt}	Ordering Code
SPL TR85	200 mW	Q65112A1150

Maximum Ratings

Parameter	Symbol		Values
Operating temperature	T_{op}	min. max.	-20 °C 60 °C
Storage temperature	T_{stg}	min. max.	-40 °C 85 °C
Peak output power	P_{opt}	max.	220 mW
Forward current	I_F	max.	260 mA
Reverse voltage ¹⁾	V_R	max.	3 V
Reverse voltage of photodiode	V_{RPD}	max.	30 V
Soldering temperature $t_{max} = 10\text{ s}$	T_S	max.	260 °C

Operation outside these conditions may damage the device. Operation at maximum ratings may influence lifetime.


Characteristics

$P_{\text{opt}} = 200 \text{ mW}$; $T_{\text{case}} = 25 \text{ °C}$

Parameter	Symbol		Values
Forward current	I_F	typ. max.	225 mA 255 mA
Peak wavelength	λ_{peak}	min. typ. max.	840 nm 850 nm 860 nm
Spectral bandwidth at 50% $I_{\text{e,rel,max}}$	$\Delta\lambda$	typ.	3 nm
Beam divergence (FWHM) parallel to pn-junction	Θ_{\parallel}	typ.	6 °
Beam divergence (FWHM) perpendicular to pn-junction	Θ_{\perp}	typ.	19 °
Monitor current ²⁾³⁾	I_m	min. typ.	300 μA 500 μA
Threshold current	I_{th}	typ. max.	56 mA 85 mA
Forward voltage	V_F	typ. max.	1.77 V 2.20 V
TE polarization	P_{TE}	typ.	20:1
Modulation frequency	f	min.	100 MHz
Thermal resistance junction case real	R_{thJC}	typ.	50 K / W


Relative Spectral Emission ⁴⁾

$$P_{\text{opt}} = f(\lambda)$$




Beam Divergence ⁴⁾

$$P_{\text{opt}} = f(\theta), T_{\text{case}} = 25^\circ\text{C}$$




Optical Output Power ⁴⁾

$$P_{\text{opt}} = f(I_F)$$




Operating Voltage ⁴⁾

$$V_F = f(I_F)$$




Threshold Current

$$I_{\text{th}} = f(T_{\text{case}});$$




Dimensional Drawing ⁵⁾




Approximate Weight: 310.0 mg

Electrical internal circuit



Pin	Description
1	LD Cathode
2	LD Anode, PD Cathode (case)
3	PD Anode

Transportation Packing and Materials ⁵⁾



Dimensions of transportation box in mm

Width	Length	Height
170 ± 5 mm	265 ±5 mm	95 ± 5 mm

Notes

Depending on the mode of operation, these devices emit highly concentrated visible and non visible light which can be hazardous to the human eye. Products which incorporate these devices have to follow the safety precautions given in IEC 60825-1.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

Important notes of operation for laser diode

a) Electrical operation

OSRAMs laser diodes are designed for maximum performance and reliability. Operating the laser diode above the maximum rating even for very short periods of time can damage the laser diode or reduce its lifetime. The laser diode must be operated with a suitable power supply with minimized electrical noise. The laser diode is very sensitive to electrostatic discharge (ESD). Proper precautions must be taken.

b) Mounting instructions

In order to maintain the lifetime of the laser diode proper heat management is essential. Due to the design of the laser diode heat is dissipated only through the base plate of the diode's body. A proper heat conducting interconnection between the diodes base plate and the heat sink must be maintained.

For further application related informations please visit www.osram-os.com/apnotes

Disclaimer

OSRAM OS assumes no liability whatsoever for any use of this document or its content by recipient including, but not limited to, for any design in activities based on this preliminary draft version. OSRAM OS may e.g. decide at its sole discretion to stop developing and/or finalising the underlying design at any time.

Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on the OSRAM OS website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office.

By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product safety devices/applications or medical devices/applications

OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

In case Buyer – or Customer supplied by Buyer– considers using OSRAM OS components in product safety devices/applications or medical devices/applications, Buyer and/or Customer has to inform the local sales partner of OSRAM OS immediately and OSRAM OS and Buyer and /or Customer will analyze and coordinate the customer-specific request between OSRAM OS and Buyer and/or Customer.

Glossary

- 1) **Reverse Operation:** Reverse Operation of 10 hours is permissible in total. Continuous reverse operation is not allowed.
- 2) **Monitor current:** Monitor current refers to a reverse voltage of $V_{RPD} = 5\text{ V}$. Monitor current is for short time power reference purpose only. Not guaranteed for accuracy.
- 3) **Monitor current:** For reference only.
- 4) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 5) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimensions are specified in mm.

Published by OSRAM Opto Semiconductors GmbH
Leibnizstraße 4, D-93055 Regensburg
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product



此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，不含有毒有害物质或元素。