

Telecoil-antennas Inductor

PAS6420V-SERIES

1. Features


1. Hearing Aid Compatibility-/Telecoil-antennas;
2. PAS6420V-series realizes small size and low profile. 6.4x2.3x2.0 mm.
3. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
4. Meets the T3/T4 FCC requirements(HAC-Act) acc. ANSI C63.19
5. High reliability -Reliability tests comply with AEC-Q200
6. Operating temperature -55~+125°C (Including self - temperature rise)



2. Applications

1. T-coil/HAC-coil for hearing and aid compatible cell phones.
2. Decoupling in RF and IF-circuit.
3. Transponder antenna.


3. Dimensions



Size	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)
PAS6420V	6.4±0.3	2.3±0.2	1.8±0.2	0.9 ref.	0.5 ref.


Unit:mm

Recommend PC Board Pattern



L(mm)	G(mm)	H(mm)
7.0	4.6	2.0

4. Part Numbering



A: Series

B: Dimension

C: Category Code

D: Inductance

E: Inductance Tolerance

L x H

V=Vehicle

702=7000 uH

K=±10%, J=±5%

5. Specification

Part Number	Inductance (uH)	f _{L0} (kHz)	SRF KHz(min)	RDC(Ω) MAX	Rated current (mA)Max.
PAS6420V-522J	5200±5%	125	520	113	30
PAS6420V-622J	6200±5%	125	488	123	30
PAS6420V-702J	7000±5%	125	420	125	20
PAS6420V-722K	7200±10%	125	450	130	15