


MULTI-BEAM

TE Internal #: 6450550-1
PCB Mount Receptacle, Vertical, Board-to-Board, 32 Position, 2.54 mm / 6.35 mm / 7.62 mm [.1 in / .25 in / .3 in] Centerline, Fully Shrouded

[View on TE.com >](#)



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**
Connector System: **Board-to-Board**
Number of Positions: **32**
Number of Rows: **4**
Centerline (Pitch): **2.54 mm, 6.35 mm, 7.62 mm [.1 in, .25 in, .3 in]**

Features

Product Type Features

Mixed & Hybrid Header	Yes
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	14
Number of Loaded Positions	32
Number of Positions	32
Number of Rows	4
PCB Mount Orientation	Vertical
Number of Power Positions	8
Number of Signal Positions	24

Electrical Characteristics

Operating Voltage	60 VDC, 200 VDC, 300 VDC
-------------------	--------------------------



Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 – 2.54 µm[50 – 100 µin]
PCB Contact Termination Area Plating Material Thickness	2.54 – 5.08 µm[100 – 200 µin]
Contact Layout	Matrix
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Receptacle
Contact Current Rating (Max)	42 A
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.076 µm[3 µin]

Termination Features

Termination Post & Tail Length	3.43 mm[.135 in]
Termination Method to PCB	Through Hole - Press-Fit

Mechanical Attachment

Mating Retention	Without
Mating Alignment Type	Guide Post
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Centerline (Pitch)	2.54 mm, 6.35 mm, 7.62 mm[.1 in][.25 in][.3 in]
Housing Material	High Temperature Thermoplastic Glass-Filled

Dimensions

Connector Width	11.94 mm[.47 in]
Connector Height	12.7 mm[.5 in]
Connector Length	86.36 mm[3.4 in]
Row-to-Row Spacing	2.54 mm[.1 in]



PCB Thickness (Recommended)	2.11 – 2.62 mm[.083 – .103 in]
-----------------------------	--------------------------------

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Glow Wire Rating	High Temperature Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	22
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts




TE Part # 7-6450550-3
[MBXL VERT RCPT 6P+48S+5P](#)




TE Part # 6450130-3
[MBXL R/A HDR 3ACP+24S+5P](#)


Customers Also Bought




TE Part #382312-009
[44A0121-24-0/9](#)




TE Part #282020-018
[44A0111-20-0](#)




TE Part #292182-8
[PLUG ASS'Y OF HYB DRAWER 12P](#)




TE Part #926882-1
[UMNL SOK 20-14 PTPBR](#)




TE Part #3-1393247-7
[W31-X2M1G-3=W23/W31](#)




TE Part #1534805-1
[HD20 COVER KIT 9POS WITH CABLE](#)




TE Part #1658683-1
[HDP-22,RCPT,SIZE 3,44 POSN](#)



TE Part #2199119-4
[M.2 0.5PITCH 3.2H KEY E 15U" AU](#)



TE Part #5535090-5
[ASSEMBLY,RECEPTACLE,EUROCARD,T](#)



TE Part #E872683001
[44A0121-22-0/9CK0001](#)

Documents

Product Drawings
[MBXL VERT RCPT 3ACP+24S+5P](#)

English

CAD Files
Customer View Model
[ENG_CVM_CVM_6450550-1_T3.2d_dxf.zip](#)

6450550-1

PCB Mount Receptacle, Vertical, Board-to-Board, 32 Position, 2.54 mm / 6.35 mm / 7.62 mm [.1 in / .25 in / .3 in] Centerline, Fully Shrouded



English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_6450550-1_T3.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_6450550-1_T3.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

[Product Specifications](#)

[Application Specification](#)

English