

DESIGN KIT

WCAP-FTBP DC Film Capacitors

MKP – Metallized Polypropylene



890 443 322 001 CS

MPPP075104J160DCPB15004

C:	100 nF
U _R :	160 V _{DC}
U _{RMS} :	90 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	300 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.1 %
	@ 100 kHz 0.26 %

890 273 322 005 CS

MPPP075154J250DCPB15004

C:	150 nF
U _R :	250 V _{DC}
U _{RMS} :	160 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	340 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.1 %
	@ 100 kHz 0.26 %

890 303 322 005 CS

MPPP075333J630DCPB15004

C:	33 nF
U _R :	630 V _{DC}
U _{RMS} :	250 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	700 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.1 %
	@ 100 kHz 0.15 %

890 273 323 004 CS

MPPP010224J250DCPB15004

C:	220 nF
U _R :	250 V _{DC}
U _{RMS} :	160 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	250 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.1 %
	@ 100 kHz 0.4 %

890 283 323 005 CS

MPPP010104J400DCPB15004

C:	100 nF
U _R :	400 V _{DC}
U _{RMS} :	220 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	300 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.1 %
	@ 100 kHz 0.35 %

Technical Data

MKP – Metallized Polypropylene

Climate Category: 40 / 105 / 56

890 443 325 010 CS

MPPP015225J160DCPB15004

C:	2200 nF
U _R :	160 V _{DC}
U _{RMS} :	90 V _{AC}
R _{ISO} :	> 10000 MΩ
dV/dt:	98 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.28 %
	@ 100 kHz 1.6 %

890 273 325 009 CS

MPPP015105J250DCPB15004

C:	1000 nF
U _R :	250 V _{DC}
U _{RMS} :	160 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	85 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.28 %
	@ 100 kHz 1.5 %

890 283 325 008 CS

MPPP015334J400DCPB15004

C:	330 nF
U _R :	400 V _{DC}
U _{RMS} :	220 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	140 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.15 %
	@ 100 kHz 0.92 %

890 303 325 010 CS

MPPP015224J630DCPB15004

C:	220 nF
U _R :	630 V _{DC}
U _{RMS} :	250 V _{AC}
R _{ISO} :	> 30000 MΩ
dV/dt:	220 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.15 %
	@ 100 kHz 0.68 %

890 273 326 007 CS

MPPP225155J250DCPB45004

C:	1500 nF
U _R :	250 V _{DC}
U _{RMS} :	160 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	61 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.4 %
	@ 100 kHz 3.4 %

- Pitch 7.5 mm
- Pitch 10.0 mm
- Pitch 15.0 mm
- Pitch 22.5 mm
- Pitch 27.5 mm

890 283 326 009 CS

MPPP225105J400DCPB45004

C:	1000 nF
U _R :	400 V _{DC}
U _{RMS} :	220 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	95 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.32 %
	@ 100 kHz 2.2 %

890 303 326 009 CS

MPPP225474J630DCPB45004

C:	470 nF
U _R :	630 V _{DC}
U _{RMS} :	250 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	130 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.28 %
	@ 100 kHz 1.5 %

890 443 327 007 CS

MPPP275685J160DCPB55004

C:	6800 nF
U _R :	160 V _{DC}
U _{RMS} :	90 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	46 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.75 %
	@ 100 kHz 5.9 %

890 283 327 008 CS

MPPP275225J400DCPB55004

C:	2200 nF
U _R :	400 V _{DC}
U _{RMS} :	220 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	98 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.4 %
	@ 100 kHz 3.4 %

890 303 327 008 CS

MPPP275155J630DCPB55004

C:	1500 nF
U _R :	630 V _{DC}
U _{RMS} :	250 V _{AC}
R _{ISO} :	> 10000 MΩ*μF
dV/dt:	130 V/μS
DF:	@ 1 kHz < 0.1 %
	@ 10 kHz 0.34 %
	@ 100 kHz 2.3 %



EMC COMPONENTS | INDUCTORS | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | LEDs | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | REDCUBE TERMINALS | CAPACITORS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2018

www.we-online.com

All products
ex stock!