



USB-C Mini Dock and Multiport Adapter - 8K HDMI, USB 3.x Gen 2 (10Gbps) Hub Ports, 100W PD Charging, HDR, HDCP 2.3

MODEL NUMBER: U442-DOCK40-5







Adds 8K HDMI, 3 USB-A hub ports and USB-C PD charging to the USB-C or Thunderbolt 3 port on your MacBook, Windows laptop or Chromebook.

Features

USB-C Mini Dock Turns Your Device's USB-C or Thunderbolt 3 Port into a Multiport Workstation This versatile 8K adapter adds multiple ports to the USB-C or Thunderbolt 3 port on your MacBook Pro,

Windows laptop or Chromebook. The U442-DOCK40-5 allows you to transmit digital audio and 8K video to an external display, add USB peripherals, and power and charge a PD Charging-compliant host device simultaneously. It is ideal for future-proofing your high-definition or Ultra HD application in anticipation of an 8K upgrade.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video Signals

By connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 8K video and digital audio to a compatible HDMI monitor, television or projector without installing special software drivers.

Enjoy the Clarity of 4K/8K Video with Multi-Channel Audio, HDR and 4:4:4 Color

The HDMI port supports 8K UHD resolutions up to 7680 x 4320 at 30 Hz for professional photo and video editing. It also supports High Dynamic Range (HDR10+), providing a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks. HDCP 2.3 compliance allows you to stream 4K content with no complications. This adapter also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

Connects USB Peripherals and Transfers Data at Fast USB 3.2 Gen 2 Speeds

Three USB 3.2 Gen 2 ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support lightning-fast data transfer rates up to 10 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. One port provides up to 5V/1.5A (7.5W) of charging power to mobile devices. The three ports share a budget of 12W (2.4A total) and support over-current and short-circuit protection.

PD 3.0 Charging Port Charges High-Powered Devices via AC Wall Charger

The USB-C Power Delivery port provides power output up to 20V 5A (100W), which is sufficient for charging and powering the connected source device, such as a MacBook or Chromebook. Just connect the device's AC wall charger to the USB-C PD port.

Ready to Use Right from the Package, So You Can Plug and Play Immediately

The plug-and-play USB-C multiport adapter is specifically designed for the MacBook Pro, Windows

Highlights

- Supports UHD resolutions up to 8K @ 30 Hz (4:4:4) for state-ofthe-art video quality
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Supports 20V 5A (100W) power output for charging the host device during use
- USB-A hub ports support lightning-fast USB 3.2 Gen 2 (10 Gbps) data transfer rates
- Complies with HDCP 2.3 standards to display up-to-date 4K/8K video content

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with HDMI input (or DVI input with use of HDMIto-DVI adapter)
- Not for use with Thunderbolt monitors

Package Includes

- U442-DOCK40-5 USB-C Multiport Adapter
- Owner's manual



laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. Its thin profile design fits easily into a pocket, purse or laptop bag for convenient connections on the go.

Specifications

OVERVIEW		
UPC Code	037332282781	
Product Type	USB Multiport Dock; Multiport Adapter	
Device Compatibility	Chromebook; Computer; DVR; Laptop; Monitor/HDTV; Phone; Projector; Tablet	
Technology	HDMI; Thunderbolt; USB 3.x	
Country/Region	Global	
Host Connector	USB C (MALE)	
VIDEO		
Video Input	USB C (MALE)	
Video Output	HDMI (FEMALE)	
Number of Monitors Supported	1	
Video Ports	HDMI (FEMALE)	
Video Ports Details	HDCP 1.4; DisplayPort 1.4; HDCP 2.3	
Resolutions Supported	x1 HDMI port supports resolutions up to 8K (7680 x 4320) @ 30 Hz	
Supported Resolutions	1280x720 (720p); 1920x1080 (1080p); 3840x2160 (4K); 5120x2880 (5K); 7680x4320 (8K)	
Max Supported Video Resolution	7680 x 4320 (8K) @ 30 Hz	
Recommended Cabling	P568-XXX-8K6 8K HDMI Cables	
Extended Mode	Yes	
Extended Mode Details	Extends an HDMI video signal from a host which supports USB-C DisplayPort Alternate Mode at resolutions up to 8K/30 Hz.	
Mirror Mode	Yes	
Mirror Mode Details	Mirrors HDMI video from a host which supports USB-C DisplayPort Alternate Mode at resolutions up to 8K/30 Hz.	
Max Supported Color Depth	36-bit Deep Color	
HDR Support	Yes	
3D Video Supported	Yes	
Chroma Sub Sampling	4:2:2; 4:4:0; 4:4:4	
EDID Support	Yes	
DisplayPort Alt Mode	Yes	
DSC Support	Yes	
DATA		





Data Ports Details INPUT Input Plug Type Input Cord Length (ft.) Input Cord Length (m) Bus Powered Battery Charging (5V/1.5A Port) Power Source Type VSB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS Number of Ports	(3) USB-A - USB 3.2 Gen 2 (10 Gbps) USB-C (MALE) 0.66 0.20 Yes Yes
Input Plug Type Input Cord Length (ft.) Input Cord Length (m) Bus Powered BATTERY Battery Charging (5V/1.5A Port) Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS	0.66 0.20 Yes
Input Cord Length (ft.) Input Cord Length (m) Bus Powered BATTERY Battery Charging (5V/1.5A Port) POWER Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification	0.66 0.20 Yes
Input Cord Length (m) Bus Powered BATTERY Battery Charging (5V/1.5A Port) POWER Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification	0.20 Yes
Bus Powered BATTERY Battery Charging (5V/1.5A Port) POWER Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS	Yes
BATTERY Battery Charging (5V/1.5A Port) POWER Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification	
Battery Charging (5V/1.5A Port) POWER Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS	Yes
Power Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification	Yes
Power Source Type USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS	
USB Power Delivery (PD) Charging Support USB Power Delivery (PD) Charging Specification CONNECTIONS	
Support USB Power Delivery (PD) Charging Specification CONNECTIONS	Bus; USB
Specification CONNECTIONS	Yes
	100W; 3.0
Number of Ports	
	5
Dock Connectors	(x3) USB-A Female; (x1) USB-C Female; (x1) HDMI Female
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	HDMI (FEMALE)
Side B - Connector 2	USB C (FEMALE)
Side B - Connector 3	(3) USB A (FEMALE)
Connector Plating	Nickel
CHARGING	
Number of Charging Ports	4
Total Charging Amps	2.4A (USB-A Hub)
Total Charging Watts	100
Charging Port Type	(3) USB A (FEMALE); (1) USB C (FEMALE)
Charging Ports	(2) USB-A: 0.9A; (1) USB-A: 5V 1.5A (7.5W); (1) USB-C: 100W (20V 5A) Power Delivery (PD 3.0)
Charging Ports Details	(1) USB-C PD 3.0 charging port supports up to 100 Watts of total charging capacity, with 15 Watts dedicated to the unit itself and 85 Watts allocated for charging a connected host device(1) USB-A port supports 5V/1.5A (7.5W) charging to a connected device(2) USB-A ports support 900mA (0.9A) maximum downstream charging and share 1.5A totalAll three USB-A ports share 12 Watts total charging capacityAll ports support short-circuit and over-current protection
Charging Ports / Amps	
Compatible Devices	(2) 0.9A; (1) 1.5A; (1) 5A





PHYSICAL		
Color	Gray	
Material of Construction	TPE+PVC+ABS	
Cable Jacket Color	Black	
Connector Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	FT2	
Cable Outer Diameter (OD)	5.0mm	
Wire Gauge (AWG)	24+34	
Cable Length (ft.)	0.66	
Cable Length (m)	0.20	
Cable Length (in.)	7.87	
Housing Color	Gray	
Cable Length (cm)	20	
Total Number of Ports	5	
Shipping Dimensions (hwd / in.)	0.87 x 7.87 x 3.54	
Shipping Dimensions (hwd / cm)	2.21 x 19.99 x 8.99	
Shipping Weight (lbs.)	0.22	
Shipping Weight (kg)	0.10	
Unit Dimensions (hwd / in.)	0.710 x 1.210 x 5.590	
Unit Dimensions (hwd / cm)	1.8 x 3.05 x 14.88	
Unit Dimensions (hwd / mm)	18 x 30.5 x 148.8	
Unit Packaging Type	Box	
Unit Weight (Ibs.)	0.201	
Unit Weight (kg)	0.09	
ENVIRONMENTAL		
Operating Temperature Range	32° to 113°F (0° to 45°C)	
Storage Temperature Range	50° to 158°F (-10° to 70°C)	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
Power Provided to Connected Device(s)	100W	
FEATURES & SPECIFICATIONS		
Overcurrent Protection	No	
Overvoltage Protection	No	





USB Hub Ports	Yes	
Number of USB Hub Ports	3	
USB Specification	USB 3.2 Gen 2 (Up to 10 Gbps)	
Data Transfer Rate	(3) 10 Gbps	
MST Support	No	
Ethernet Support	No	
UASP Support	No	
Auto MDIX Support	No	
Full Duplex Support	No	
HDCP Specification	1.4; 2.3	
Driver Required	No	
STANDARDS & COMPLIANCE		
TAA Compliant Option	Ν	
Product Certifications	EN 55032; ICES (Canada)	
Product Compliance	CE (Europe); FCC Part 15 Class B (USA); REACH; RoHS3; UKCA; WEEE	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	1-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.