

NetCommander 16-Port Cat5 KVM Switch 1U Rack-Mount with PS2 to USB Input Adapter

MODEL NUMBER: B072-016-1A



Features

- Expandable - Cascade a second level of KVM switches to control up to 256 servers from a single station
- Extend distance: between computer and switch up to 30 meters/100 ft.
- Rack mountable: sleek, 1U space saving KVM switches
- Accepts PS2 Mouse and Keyboard (or USB Mouse and Keyboard with included adapter)
- Innovative CAT5 technology: eliminate cable clutter at the rack
- Multi-layer security: protects your corporate data
- Easy server management: choice of On Screen Display, Hot-key, or push button control
- Multi-platform: PS/2 and USB support
- To convert DisplayPort or HDMI computers to VGA, use adapters P134-06N-VGA-V2 or P131-06N. Maximum video resolutions using adapters may vary.
- Add Model B021-000-19 for space saving, in-the-rack, LCD, Keyboard and Mouse
- Compact Size: 17"W x 5"D x 1.75"H
- Video Resolution: 1600x1200@75Hz
- Internal Power Supply
- Compatible with all major operating systems
- Constructed of heavy-duty steel housing

Note: B051-000 remote access IP unit is not compatible with B072-016-1A 1U Rack-Mount NetCommander Cat5 KVM Switch Series.

Highlights

- 16 RJ45 Ports utilize inexpensive Cat5 patch cables
- Expandable - Cascade a second level of KVM switches to control up to 256 servers from a single station
- Accepts PS2 or USB Mouse and Keyboards with included Adapter

System Requirements

- Computers: The B078-101-USB-1 Server Interface Module must be used to connect a server to the server ports on the KVM switch.
- For computers with DisplayPort or HDMI, change to VGA using adapters P134-06N-VGA-V2 or P131-06N. Maximum video resolutions using adapters may vary.
- Compatible with all major operating systems

Package Includes

- 16-Port NetCommander 1U Rackmount Cat5 KVM Switch
- PS2 to USB Adapter
- 6-ft. (1.83 m) Power Cord
- 6-ft. (1.83 m) Firmware Upgrade Cable
- Rackmount Bracket kit

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332186607 |
| Max CPU | 256 |



Powering Business Worldwide



| | |
|--|---|
| Technology | Cat5/5e; PS/2; VGA/SVGA |
| VIDEO | |
| Max Supported Video Resolution | 1600 X 1200 @ 75 Hz |
| Max. Distance (Between any 2 Units) | 100 ft (30.5m) |
| Max Number of Ports (Entire Chain) | 256 |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| Input Frequency | 50/60Hz |
| Input Current | 120V (0.7A) / 230V (0.3A) |
| Power Input Receptacle | IEC-320-C14 |
| POWER | |
| Power Consumption (Watts) | 8 |
| CONNECTIONS | |
| Number of Ports | 16 |
| PC/Server Connections | PS/2; USB; VGA |
| Side A - Connector 1 | HD15 (FEMALE) |
| Side A - Connector 2 | (2) MINI DIN-6 (FEMALE) |
| Side A - Connector 3 | RJ11 (FEMALE) |
| Side B - Connector 1 | (16) RJ45 (FEMALE) |
| Computer Keyboard and Mouse Interface | PS/2; USB |
| Computer Monitor Interface | VGA |
| Console Keyboard and Mouse Interface | PS/2; USB |
| Console Monitor Interface | VGA |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Green(CPU ON, SELECTED) |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Steel (Steel, Electrogalvanized, Cold Rolled, Coil) |
| Rackmountable | Yes |
| Shipping Dimensions (hwd / in.) | 4.33 x 20.28 x 7.68 |
| Shipping Dimensions (hwd / cm) | 11.00 x 51.51 x 19.51 |



Powering Business Worldwide



| | |
|--------------------------------------|---|
| Shipping Weight (lbs.) | 5.45 |
| Shipping Weight (kg) | 2.47 |
| Unit Dimensions (hwd / in.) | 1.710 x 16.780 x 4.770 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 3.70 |
| Unit Weight (kg) | 1.68 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | -40° to 158°F (-40° to 70°C) |
| Relative Humidity | 0% to 80% RH, Non-Condensing |
| BTUs | 27.3 BTU/Hr |
| COMMUNICATIONS | |
| IP Remote Access | No |
| PORT EXPANSION | |
| Daisy-chainable or Cascadable | Cascadeable |
| FEATURES & SPECIFICATIONS | |
| NIAP-Certified Secure | No |
| Number of Users | 1 |
| On-Screen Display (OSD) | Yes |
| Port Selection | Pushbutton; Hotkey; OSD |
| Driver Required | No |
| Recommended Category Cable | Cat5e/6 Cables |
| STANDARDS & COMPLIANCE | |
| Product Certifications | CAN/CSA C22.2; CAN/CSA-C22.2 No. 60950-1 (Canada); UL 60950-1 |
| Product Compliance | RoHS; CE (Europe); REACH; FCC Part 15 Class A (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.