

# WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor for measuring loads on the rotor blade of wind turbine generators. Robust (can be stood on). With magnetic shielding. Cable resistance compensation thanks to 6-wire connection technology.

## Product description

WIL-RM-S-SG-R1 is an optimized sensor with integrated strain gauges specifically designed for use in wind turbine generators. The sensor is adhered to the inner side of the rotor blade near the base of the blade. In conjunction with a WIL-BI switchgear and controlgear assembly, loads on the rotor blade can be measured and evaluated. This allows the wind turbine generator to be controlled with load optimization, reducing the load on the rotor blades to a minimum.

The sensor is part of the Blade Intelligence rotor blade monitoring system for wind turbine generators (WTGs). The Blade Intelligence rotor blade monitoring system allows for recording and detailed analysis of typical measured values for lightning currents, temperature, ice thickness, and bending moments on the rotor of a WTG. It consists of the corresponding sensors, preassembled connecting cables, and a WIL-BI switchgear and controlgear assembly (as the evaluation unit).

## Your advantages

- Robust sensor for use in the rotor blade of a WTG
- Proactive monitoring of the rotor blade
- Proven technology, optimized for the wind industry

## Commercial data

Item number	1183803
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DT02
Product key	DTHABA
GTIN	4063151222420
Weight per piece (including packing)	0.6 kg
Weight per piece (excluding packing)	0.6 kg
Customs tariff number	90303320
Country of origin	DE

## Technical data

### Product properties

Product type	Sensor
--------------	--------

### Dimensions

#### External dimensions

Width / Height / Depth	48 mm / 10 mm / 130 mm
------------------------	------------------------

### Cable/line

#### Cable entry

Connection method	M12 connector, 8-pos. (A-coded)
-------------------	---------------------------------

### Characteristics

#### Measuring system

Elongation: Working elongation	max. 800 µm/m (at 10 <sup>8</sup> load cycles)
Elongation: Elongation at break	2500 µm/m
Resistance:	350 Ω ±0.3 %
Resistance: Offset	max. ± 3.5 Ω
K-factor:	approx. 2 ... 2.2 (see sensor rating plate)
Coefficient of expansion:	10.8 10 <sup>-6</sup> K <sup>-1</sup>

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Shock (operation)	30g (in accordance with EN 60068-2-27/IEC 60068-2-27)
Vibration (operation)	5g (in accordance with EN 60068-2-6/IEC 60068-2-6)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3,000 m above mean sea level; at >3,000 m above mean sea level observe derating)

# WIL-RM-S-SG-R1 - Sensor



1183803

<https://www.phoenixcontact.com/us/products/1183803>

## Classifications

### ECLASS

ECLASS-13.0	27143137
-------------	----------

### ETIM

ETIM 9.0	EC000926
----------	----------

### UNSPSC

UNSPSC 21.0	43201500
-------------	----------

# WIL-RM-S-SG-R1 - Sensor



1183803  
<https://www.phoenixcontact.com/us/products/1183803>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)