SIEMENS

Data sheet

6GF6710-3BG

PS2 keyboard 19" INT, with trackball, removable keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



Figure similar

General information		
Product type designation	PS/2 built-in keyboard INT	
Control elements		
Keyboard fonts		
• Design	Membrane keyboard	
 Keyboard assignment 	B3F, 101/102 or 104/105 OMRON	
Color of the buttons	light gray	
Color of the key inscription	Black	
Key illumination	No	
Function keys		
 — Number of function keys 	12	
— Programmable	Yes	
Number pad	Yes; Free-standing	
 status LED displays 	Yes; Num, Caps and Scroll	
— for number pad	Yes	
— for Shift keys	Yes	
Connection type		
• USB	Yes; With PS/2 USB adapter (not included in the scope of supply)	
• PS/2	Yes	
Frame size/design		
Standard	Yes; For industrial applications	
• 19" keyboard	Yes	
Installation type/mounting		
Rack mounting	No	
Front mounting	Yes	
Wall mounting/direct mounting	No	
Input current		
Current consumption (rated value)	35 mA; Typical	
Battery		
Battery-operated	No; maintenance-free	
EMC		
Emission of radio interference acc. to EN 55 011		
 Limit class A, for use in industrial areas 	Yes	
Degree and class of protection		
IP (all-round)	IP65 when the ball is actuated; mouse only IP55	
Splashproof	Yes	
Standards, approvals, certificates		
CE mark	Yes	
RoHS conformity	Yes	

Ambient conditions	
Ambient temperature during operation	
• min.	0°0
• max.	40 °C
Ambient temperature during storage/transportation	
• min.	-10 °C
• max.	50 °C
Relative humidity	
• Operation, max.	90 %; no condensation
Condensation permissible	No
Operating systems	
Runs under operating system	
Windows CE	Yes
Windows Vista	Yes
Windows XP	Yes
• Windows 7	Yes
Windows 10	Yes
Mechanics/material	
Material	
Sheet steel	Yes
Enclosure material (front)	
Plastic	Yes; AUTOTEX (R) V150
Service life	
 Number of operating cycles, keys 	1 000 000; Operations (minimum)
Dimensions	
Width	482.6 mm
Height	38 mm
Depth	177.8 mm
Weights	
Weight (without packaging)	1 490 g
Weight (with packaging)	1 735 g
Scope of supply	
Delivery quantity in pieces	1; Built-in keyboard with stud bolts
Other	
Merchandise	Yes; TIPRO no. K-842 (K-642)
Manufacturer name	TIPRO Representative Office
Manufacturer's address	Vogelweg 20, 31785 Hameln, Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62
Usable in the following products	
Product 1	6AV2124-0GC13-0AX0
Product 2	6AV2124-0QC13-0AX0
last modified:	9/29/2021 🖸